

**ROBINAIR****INFRARED REFRIGERANT  
LEAK DETECTOR**

Locate the exact location of the leak

# Find Leaks Faster

## Eliminate countless hours searching for hard to find leaks



### LEAK DETECTOR FEATURES

- Advanced infrared sensor designed to last a minimum of 10 years.
- Three sensitivity levels down to 0.15 oz./year.
- Automatically recalibrates in highly contaminated areas to help pinpoint the exact location of the leak
- Won't trigger on oil or moisture.
- Senses CFC, HFC, HCFC blends and HFO-1234yf refrigerants.
- 8-hour lithium ion battery lasts all day long and beyond.
- Visual alert and peak button make it easy to find leaks in noisy environments.
- Audible alert with mute button.
- Magnetic hanger to easily hang the unit during leak repair.
- Durable carrying case let's you easily store leak detector and accessories.
- Meets NEW SAE J2913 standard for 1234yf and previous SAE J2791 standard for 134A.



Meets NEW SAE J2913 standard for 1234yf.

Leak Detector

**Specifications**

Gases measured: CFC, HFC, HCFC blends and HFO-1234yf.  
 Sensing element: Infrared  
 Response time: 0.5 to 1 second.  
 Sensitivity levels: HIGH 0.15 oz./year and higher  
 MEDIUM 0.25 oz./year and higher  
 LOW 0.5 oz./year and higher  
 Accuracy: Meets current SAE J2791 and J2913 standards.  
 Calibration: Automatic

Warm up time: 30 seconds  
 Probe length: 15 inches  
 Battery type: 3.7VDC(nominal) rechargeable lithium-ion battery.  
 Battery life: Approximately 8 hours when fully charged.



12-136 ©2012 Robinair.