

ROBINAIR

Fully automatic, unmatched 98.5% recovery

Robinair introduces its next innovation, the 34788NI and 34788NI-H, featuring an industry-leading 98.5% recovery efficiency for standard and hybrid vehicles and fully automatic function.



Robinair 34788NI and 34788NI-H machines recover, recycle, evacuate, leak-test and recharge R-134a with improved 98.5% efficiency – unmatched by any competitor. The new design features a larger graphical display, automatic features including leak testing, automatic refrigerant refill and oil drain/inject – putting A/C lubricant back into the system. The 34788NI and 34788NI-H also boasts the ability to add a printer, USB data sharing, refrigerant identifier and wireless module for Wi-Fi or Bluetooth® communication. An optional refrigerant charge and oil capacities database is available for North American market vehicles.

Robinair A/C service tools and equipment are sold through distribution partners, resellers and retailers. Visit robinair.com to find a partner near you.

34788NI shown

ROBINAIR.COM / 800.533.6127 /   

Industry-leading efficiency and more accurate service



Features	34288	34988	34788NI	34788NI-H
Fully-Automatic Function: Program to recover, vacuum, leak test and charge without operating panel valves.		×	×	×
Automatic Dye Inject: Gives the user the ability to use the machine to inject UV dye into a vehicle's A/C system.		×		
Automatic Oil Drain: A display reminds you to empty the graduated container to show the amount of oil to replace.	×	×	×	×
Oil Inject: Automatically inject oil back into the vehicle's A/C systems.		×	×	
Refrigerant & Oil Database: A/C system capacities for North American market vehicles (Optional – not included with the machine)		Optional	Optional	Optional
A/C System Flush: Flushes a vehicle's A/C system with refrigerant, eliminating any residual oil or other liquid. (Flushing adapters not included)		×	×	×
Save & print before and after service data: Allows the user to store before and after service information by vehicle and print this information to provide to a customer.		×	×	×
Visual & Audible Alarm: Notifies the user when service is complete, or if a problem has occurred.		×	×	×
Vacuum Leak Test: Monitors level after evacuation, informs of possible leak.	×	×	×	×
Automatic Air Purge: Eliminates system-damaging air without monitoring gauges or opening valves.	×	×	×	×
Automatic Refrigerant Refill: Maintains a user-selectable amount of refrigerant in an internal vessel and signals when it's time to change supply tank, no monitoring required.		×	×	×
Vacuum Feature: Defaults to 15 mins, programmable up to 99 mins. "Remaining time" is displayed.	×	×	×	×
Display: Multilingual.	×	×	×	×
Refrigerant Charging: Select a charge mode from high or low side, or use both sides.		×	×	×
Refrigerant Management System: Displays refrigerant use and monitors remaining filter life. Prompts appear when 1/3 of filter life remains.	×	×	×	×
Electric Vehicle: Capable of servicing high voltage electric compressor A/C systems.				×
Printer		×	Optional	Optional
Refrigerant Identifier			Optional	Optional

Related Service

Get filters before the beginning of the season for preventative maintenance

- Keep recovery and recycling units operating at peak efficiency with a convenient maintenance kit.
- Contains one quick change filter-drier to be used on both R-12 and R-134a stations, and one 16 ounce bottle of our Premium High Vacuum Pump Oil.



34724
(filter-drier)



13172
(filter-drier & oil)